

**DESCRIPTION**

Total thickness	EN 428	mm	2.00
Weight	EN 430	g/m <sup>2</sup>	3360
Width of sheet	EN 426	cm	
Length of sheet	EN 426	lm	
Tile size	EN 427	mm	608 x 608
Number of tiles per package	-	-	20


**CLASSIFICATION**

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
K rating	-	class	K5
Fire rating	EN 13 501-1	class	B <sub>fl</sub> -s1
Critical radiant flux	ASTM E648	W/cm <sup>2</sup>	
Static electrical propensity	EN 1815	kV	< 2

**PERFORMANCE**

Wear resistance	EN 660.2	mm	≤ 0.30
Wear Group	EN 649	group	M
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	~ 0.03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal treatment	-	-	OK
Surface treatment	-	-	PU

**CE MARKING**

<b>CE</b>	EN 14041	-	
		-	